




# HIGH PERFORMANCE VPCI® PACKAGING

# Cor-Pak® VpCI® Polycoated Paper Corrosion Inhibiting Barrier Paper



#### PRODUCT DESCRIPTION

Cor-Pak VpCI Polycoated Paper is the premium corrosion inhibiting polycoated paper in the industry. Our patented Vapor phase Corrosion Inhibiting technology has revolutionized the way metals are protected in an enclosed package. Cortec Cor-Pak VpCI Polycoated Paper provides superior corrosion protection for both ferrous and non-ferrous metals, which eliminates the need to inventory a variety of papers for all the different types of metal you need to protect.

In addition, Cor-Pak VpCl Polycoated Paper is coated with a polyethylene coating, to provide a moisture barrier and/or moisture-vapor barrier.

Cortec® Cor-Pak VpCl Polycoated Paper is produced with the highest quality neutral natural kraft paper, and offers exceptional resistance to water, oil and grease. Parts, protected with Cor-Pak VpCl Polycoated Paper can be painted, welded, and soldered. The thin protective film doesn't influence physical properties of most sensitive electrical and electronic components, including conductivity and resistance. In addition, the paper basestock for the VpCl coating is produced with closely packed cellulose fibers which form a relatively non-permeable sheet.

#### TYPICAL APPLICATIONS

Cortec<sup>®</sup> Cor-Pak VpCl Polycoated Paper can be used to protect products for storage and shipment in a wide variety of ways: end closures for shipping tubes; insert strips for recessed areas in large packages; and as sheet liners or separators between products.

The typical applications are:

- Metals industry: coils, wire reels, plate, bar, etc.
- Metal forging and die casting: raw and machined forgings and castings.
- Metalworking: stamping, sheet metal work, springs, bearings, fasteners, tube, pipe, jewelry, silverware, etc.
- Finished products: engines, machinery, equipment, tools, hardware, appliances, instruments, motors, etc.
- Electrical and electronic components, controls, printed circuit boards, etc.

# **FEATURES**

- One product for all ferrous and non-ferrous metals.
- Contains no nitrites, phosphates, silicones, chromates or other heavy metals.
- Effective against aggressive environments including humidity, SO<sub>2</sub>, H<sub>2</sub>S and galvanic corrosion from dissimilar metals.
- Conforms to military specifications MIL-P-3420E.
- Protective film does not need to be removed prior to further surface finishing or coating application.
- Protects dry or oiled metals during storage, transit and overseas shipment.
- Good moisture barrier and resistant to oils.
- Natural grade paper eliminates package contamination.
- Combines corrosion protection, barrier properties, and packaging into one step.



#### **PHYSICAL PROPERTIES**

Test Method	Result
Tear Test, ASTM D-689 (gf)	131/120*
MVTR, ASTM F-1249 @ 100f, 90%	1.8
R.H. (g/100in²/day • D)	

<sup>\*</sup>Machine Direction/Cross Direction

# **METHOD OF APPLICATION**

Products should be packaged as soon after cleaning as possible. Keep the VpCI paper as close to the surface of the product as practical, leaving no barrier between the VpCI paper and the metal surface to be protected.

Use approximately 1 square foot (0.09 m²) of VpCl paper for every 3 square feet (0.28 m²) of surface to be protected, and 1 square foot (0.09 m²) of VpCl paper for every 0.5 cubic foot (0.01 m²) of void space. For long-term storage of up to ten years, enclose the wrapped product in an airtight package.

Standard construction of Cor-Pak VpCl Polycoated Paper: Neutral natural paper coated on one side with VpCl material and with polyethylene on the reverse side.

#### **METALS PROTECTED**

- Carbon Steel
- •Stainless Steel
- Galvanized Steel
- Cast Iron
- Aluminum Alloys
- Copper
- Brass (≤30% Zn)
- Solder

#### **PACKAGING AND STORAGE**

Custom sizes and constructions available upon request.

FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY SEALED
NOT FOR INTERNAL CONSUMPTION
CONSULT MATERIAL SAFETY DATA SHEET FOR MORE
INFORMATION

# **LIMITED WARRANTY**

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA Phone (651) 429-1100, Fax (651) 429-1122 Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com Internet http://www.CortecVpCl.com

printed on recycled paper 10% post consumer
Revised 7/28/03. Cortec Corporation 2003. All rights reserved. Supersedes: none
Cortec® and YpCI® are trademarks of Cortec Corporation



OTiK Sp. z o.o. ul. Hutnicza 4

ul. Hutnicza 4 81-061 Gdynia tel.: 58 6230498 fax: 58 6230496

otik@use.pl

www.inhibitory.use.pl











