



VpCI™ METALWORKING PRODUCTS

EcoLine™ Long-Term Rust Preventative



PRODUCT DESCRIPTION

EcoLine™ Long Term Rust
Preventative is a biodegradable
temporary coating designed for use
in severe marine and high humidity
outdoor and indoor environments.
It protects against all types of
corrosion and oxidation, and works
well on a variety of metals. Its
excellent penetrating properties aid
in loosening frozen or rusted parts.

EcoLine[™] products are based on soybean derivatives and soybean methyl esters. Methyl esters have been used in this revolutionary, low-impact technology as the solvent carrier. These soya-based products provide excellent lubricity and biodegradability. EcoLine[™] products are better for the environment and leave behind a high-performance VCI corrosion protection layer.

FEATURES

- Complete multimetal protection
- Environmentally friendly and biodegradable
- Safe for users
- VOC-free
- Provides universal corrosion protection
- Combines film-forming additives with vapor corrosion inhibitors (VCIs)
- Provides excellent anti-corrosion protection in high humidity atmospheres and choride-containing environments
- Excellent lubricity
- Good replacement for mineral oil and flammable solvents

TYPICAL APPLICATIONS

- Machines and equipment
- Maintenance
- Temporary coating for storage and shipment
- Wire
- Sheet metals
- Pipe
- Flanges
- Gears
- Fabricated or machined parts

APPLICATION

EcoLine[™] Long Term Rust Preventative is a ready-to-use product and can be applied by dipping, spraying or brushing at many stages of metal fabrication, storage or shipment.

METALS PROTECTED

- Carbon steel
- Aluminum and alloys
- Copper and alloys
- Cast iron
- Galvanized steel
- Stainless steel

TYPICAL PROPERTIES

Appearance Clear amber liquid

Non-volatile Content 95-100%

Density 7.3-7.5 lb/gal (0.87-0.90 kg/l)

STORAGE AND PACKAGING

EcoLine™ Long Term Rust Preventative is packaged in 16 oz. (455 ml), 5 gallon (19 liter) pails, 55 gallon (208 liter) drums, liquid totes and bulk. The product should be remain sealed before storage. The shelf life of EcoLine™ Long Term Rust Preventative is up to 24 months.

Note: Please see the Material Safety Data Sheet (MSDS) for proper handling of product.



FOR INDUSTRIAL USE ONLY KEEP OUT OF REACH OF CHILDREN KEEP CONTAINER TIGHTLY CLOSED NOT FOR INTERNAL CONSUMPTION CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA Phone (651) 429-1100, Fax (651) 429-1122 Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com Internet http://www.cortecvci.com

Distributed by:



OTiK Sp. z o.o.

ul. Hutnicza 4 81-061 Gdynia tel.: 58 6230498 fax: 58 6230496

otik@use.pl

www.inhibitory.use.pl









