

# ElectriCorr® VpCI™ -248



## PRODUCT DESCRIPTION

Designed for use in a sheltered environment, ElectriCorr® VpCI™ -248's continuous vapor action saves money by extending product life and eliminating downtime due to corrosion. ElectriCorr® VpCI™ -248 forms a molecular film effective against aggressive environments, including industrial, marine and tropical climates. This film does not alter the electrical, resistance or magnetic properties. ElectriCorr® VpCI™ -248 can be safely applied for protection of even low-voltage circuits or relays without causing any changes in conductivity. It can be safely used with plastics, elastomers and other non-metallics. In addition to corrosion protection, ElectriCorr® VpCI™ -248 is an excellent contact cleaner of oils, grime and other contaminants.

ElectriCorr® VpCI™ -248 is an effective inhibitor of galvanic corrosion for most metals and alloys normally found in electronics applications, such as aluminum, copper, ferrous and non-ferrous metals. Application provides instant corrosion protection. ElectriCorr® VpCI™ -248 is thermally stable, non-flammable, and based on environmentally sensible fluorocarbon solvents, which are exempt from VOC regulations by the US EPA.

## FEATURES

- Non-flammable
- Instant corrosion protection
- Long-term protection
- Minimized field service
- Increased corrosion protection at a lower cost than conventional rust preventives
- CFC and 1,1,1-Trichlorethane-free
- Not listed as ODP, MAP or SARA reportable
- The carrier solvents are exempt from VOC regulations by the US EPA (October 8, 1996, September 24, 1997, Federal register)
- Vapor phase protection in vented or unvented enclosures
- May be used as a cleaning and defluxing agent
- Moisture-displacing and penetrating film characteristics

## TYPICAL APPLICATIONS

- Ideal for general and precision cleaning
- Printed circuit boards
- Electrical contacts and components
- Electric motors
- Protects copper bearings, ferrous and non-ferrous metals, aluminum, etc.
- Can be used in contact with majority of engineering plastics, elastomers and other non-metallics
- Generators and junction boxes
- Spray for use after final assembly or in the field

## APPLICATION

Spray a very light mist over the area needing protection.

**Note:** Application of a heavy mist will result in a heavy film that sags and remains wet. More is not necessarily better and could cause fouling or other complications of electrical connections.

Application is effective for 6+ months with proper controls.

## PACKAGING AND STORAGE

ElectriCorr® VpCI™ -248 aerosol spray is available in cartons of six 12 oz. (340 gram) cans. ElectriCorr® VpCI™ -248 should be kept from high temperatures and in normal warehouse conditions to prevent from freezing. ElectriCorr® VpCI™ -248 has a shelf-life of 3+ years in sealed packages.

## PHYSICAL PROPERTIES OF LIQUID

Appearance Clear slightly yellow liquid  
Non-volatile Content 6-8%  
Density 11.0-11.5 lb/gal (1.32-1.38kg/l)

Resistance Change of Applied Film	
Time (Minutes)	Resistance (ohms)
Initial	Over 20 megohms
Immediate	7.83 megohms
1 minute	8.71 megohms
2 minutes	10.96 megohms
3 minutes	12.36 megohms
4 minutes	14.40 megohms
120 minutes	Over 20 megohms

## FOR INDUSTRIAL USE ONLY

**KEEP OUT OF REACH OF CHILDREN**

**KEEP CONTAINER TIGHTLY CLOSED**

**NOT FOR INTERNAL CONSUMPTION**

**CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION**

## LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

**BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.** No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

**THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.**



4119 White Bear Parkway, St. Paul, MN 55110 USA  
Phone (651) 429-1100, Fax (651) 429-1122  
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com  
Internet <http://www.CortecVpCI.com>

printed on recycled paper 10% post consumer  
Revised 10/21/02, Cortec Corporation 2002. All rights reserved. Supersedes: None.  
ElectriCorr® and VpCI™ are trademarks of Cortec Corporation.

Distributed by:



OTiK Sp. z o.o.

ul. Hutnicza 4  
81-061 Gdynia  
tel.: 58 6230498  
fax: 58 6230496

[otik@use.pl](mailto:otik@use.pl)

[www.inhibitory.use.pl](http://www.inhibitory.use.pl)



Certificate No.70781

Certificate No.81867