

VpCI ADDITIVES FOR COATINGS, FLUIDS, ADHESIVES AND PLASTICS

M-238

PRODUCT DESCRIPTION

M-238 is a solvent-based blend of contact and vapor phase inhibitors designed as an additive to aromatic, paraffinic, naphthenic, fluorocarbon and hydrocarbon-based products. It provides multimetal protection during operating and idle conditions. M-238 leaves a very thin film on ferrous and nonferrous metal surfaces, which protects metals even in very humid atmospheres.

FEATURES

- Stable in hydrocarbon solutions
- Can be blended at every stage of production
- Works as a thin self-healing film
- Environmentally friendly
- Low VOC
- Protection is immediate
- Contains contact and vapor phase inhibitors
- Provides multimetal protection
- Effective at low concentrations
- Compatible with many antioxidants, EPs, anti-scuff products and other hydrocarbon-based additives
- Can be painted over*

*Tests show when M-238 was added to a naphthenic-based cleaner up to 5% by weight, there was no decrease in adhesion for a permanent acrylic-based topcoat on carbon steel.

TYPICAL APPLICATIONS

Use M-238 as an additive to:

- Solvents
- Synthetic formulations
- Hydrocarbon formulations
- Add to solvent or oil-based fluids @ 1-4% by weight

TYPICAL PROPERTIES

Appearance Non-volatile Content pH Density Clear yellow liquid 70-75% 8.5-9.0 (1% aqueous) 7.5-7.6 lb/gal (0.89-0.91 kg/l)



TYPICAL PERFORMANCE PROPERTIES

M-238 was added at 4% to a synthetic hydrocarbon (S.H.) and a hydrocarbon cleaner. The panels coated with these solutions were tested. Results are in hours until failure. Failure is defined as the onset of visual corrosion.

	S.H.	S.H. + 4% M-238	Gunk®**	Gunk® + 4% M-238
Carbon Steel 1010	48	300+	120	240+
Castiron	1	72	N.T.*	N.T.
Al. 3003 H14	3	72	N.T.	N.T.
Castaluminum	N.T.	N.T.	24	120+
Copper	70	150+	96	240+
Galvanized steel	70	150+	N.T.	N.T.

*Not tested

**Gunk® is a hydrocarbon-based automotive engine cleaner manufactured by E.A.C. of Stafford, England. Note: Expect a slight to moderate increase in performance when tested in salt spray environments

FOR INDUSTRIAL USE ONLY KEEP OUT OF REACH OF CHILDREN KEEP CONTAINER TIGHTLY CLOSED NOT FOR INTERNAL CONSUMPTION CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec[®] products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA Phone (651) 429-1100, Fax (651) 429-1122 Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com Internet http://www.cortecvci.com

printed on recycled paper in 10% post consumer Revised 1/30/01. Cortec Corporation 2001. All rights reserved. Supersedes: 4/10/98. Distributed by:



Certificate No. 7078