



PRODUCT DESCRIPTION

M-381

M-381 is a water-based corrosion inhibitor additive designed for waterborne coatings or compounds. M-381 should be used with carboxylated acrylic or styrene-acrylic latices. No ammonia is present in this additive.

FEATURES

- Provides coatings with excellent corrosion resistance
- Can be post-added to batch
- Low viscosity
- Improves salt spray, humidity resistance and prohesion
- Minimal odor
- Prevents flash rusting
- LowVOC
- Effective on carbon steel, cast iron, aluminum, and galvanized steel

PHYSICAL PROPERTIES

Appearance	Tan color liquid
Density	9.0-10.0 lb/gal
	(1.08-1.20 kg/l)
Non-volatile Content	70-74%
VOC	1.2 lb/gal (0.14 kg/l)
pН	9.8-10.3 (1% aqueous)

PACKAGING AND STORAGE

M-381 is available in 5 gallon (19 liter) plastic pails, 55 gallon (208 liter) drums, liquid totes and bulk. Shelf life is 12 months.



FOR INDUSTRIAL USE ONLY KEEP OUT OF REACH OF CHILDREN KEEP CONTAINER TIGHTLY CLOSED NOT FOR INTERNAL CONSUMPTION CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec[®] products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA Phone (651) 429-1100, Fax (651) 429-1122 Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com Internet http://www.CortecVpCl.com

printed on recycled paper 10% post consumer Revised 9/3/02. Cortec Corporation 2002. All rights reserved. Supersedes: None. Distributed by:



OTiK Sp. z o.o. ul. Hutnicza 4 81-061 Gdynia tel.: 58 6230498 fax: 58 6230496

otik@use.pl www.inhibitory.use.pl





Certificate No.81867

ISO 9001 Certificate No.70781