



VCI ADDITIVES FOR FORMULATORS

S-7

PRODUCT DESCRIPTION

S-7 is an oxygen scavenger designed to protect low to medium pressure boiler systems against corrosion. Oxygen present in feed water can cause severe damage to boiler equipment if left unchecked. An oxygen induced attack can lead to pitting corrosion on the metal surface, which can result in rapid failures of the boiler.

FEATURES

- Economical
- Safe to use
- Easy control
- Effective against dissolved oxygen

TYPICAL PROPERTIES

Appearance	White powder
pH	9.5-10.0 (1% aqueous)

DOSAGE

The dosage will vary depending on the amount of dissolved oxygen in the boiler water. A starting dosage of S-7 is 100 ppm. S-7 should continue to be added until zero dissolved oxygen level is reached in the boiler water. Test kits can be purchased from companies such as the HACH Company to monitor the level of dissolved oxygen.

FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA
 Phone (612) 429-1100, Fax (612) 429-1122
 Toll Free (800) 4-CORTEC, E-mail info@corotecvci.com
 Internet <http://www.corotecvci.com>

Distributed by:
OTiK Sp. z o.o.
 ul. Hutnicza 4
 81-061 Gdynia
 tel.: 58 6230498
 fax: 58 6230496



otik@use.pl
www.inhibitory.use.pl



printed on recycled paper 10% post consumer

Revised 7/2/98. Cortec®, Corwipe®, EcoSpray®, EcoWeave®, MCI®, Cor-Lube™, Cor-Mastic™, Cor-Pak™, Corrosobars™, EcoCoat™, EcoShield™, ElectriCor™, Migrating Corrosion Inhibitors™, Migratory Corrosion Inhibitors™, PrimeCoat™, Total Corrosion Control™, VCI Film Color of Blue™ and VHDRS™ are trademarks of Cortec Corporation. ©Cortec Corporation 1998. All rights reserved. Supersedes: 4/1/98.



Certificate No. 43345