



## HIGH PERFORMANCE VpCI™ COATINGS

# VpCI®-373

### PRODUCT DESCRIPTION

VpCI®-373 is a water-based wash primer. VpCI®-373 is used for bonding other primers and coatings such as VpCI®-386 to a variety of metal substrates. VpCI®-373 is applied at an extremely thin thickness of 0.5-1.0 mil (12.5-25 microns) DFT. When used in conjunction with topcoats, this product can extend protection significantly.

### FEATURES

- Excellent replacement for chromate treatments
- Good adhesion on surfaces which are difficult to adhere to
- Multimetal protection
- Excellent primer for aluminum
- Conforms to MIL-P-15328D
- NSN #8010-01-470-2739

### TYPICAL PROPERTIES

#### VpCI®-373 Green

Appearance	Opaque olive green liquid
Shelf Life	12 months @ 75°F (24°C)
Non-volatile Content	38-50%
Theoretical Spread Rate	1054 ft <sup>2</sup> /gal @ 0.5 mils DFT (26 m <sup>2</sup> /l @ 12.5 microns)
Density	9.7-10.1 lb/gal (1.16-1.21 kg/l)
VOC	0.17 lb/gal (20 g/L)

#### VpCI®-373 Clear

Appearance	Milky white liquid (dries clear)
Shelf Life	12 months @ 75°F (24°C)
Non-volatile Content	40-50%
Theoretical Spread Rate	1054 ft <sup>2</sup> /gal @ 0.5 mils DFT (26 m <sup>2</sup> /l @ 12.5 microns)
Density	8.5-8.6 lb/gal (1.02-1.03 kg/l)
VOC	0.17 lb/gal (20 g/L)

### APPLICATION

#### Surface Preparation:

Surface must be equivalent to NACE #3 or SSPC SP2.

NACE - National Association of Corrosion Engineers  
SSPC - Steel Structure Painting Council

#### Product Preparation:

Product must be mixed prior to use as settling occurs over time.

#### Product Application:

Product can be applied by spray, brush, roll or dip. Normal WFT is 2.5 mils (62.5 microns) yielding 0.5 mil (12.5 microns) DFT.

#### Spray Application:

Mils/Pass	2.5 mils (62.5 microns) WFT
Model	AA Plus for premium finish 510 (Airless) for other uses
Pump	30:1 President SST
Tip	0.009"-0.013" (0.023-0.033 cm)
Cap	Standard
Filter	60 Mesh SST
Air Pressure	100 psi (69 bar) AA 2,000-2,500 psi (138-172 bar) Airless
Fluid Hose	3/8" SST Teflon
Fluid Pressure	1000-1500 psi (69-103 bar) AA

#### Product Clean-up:

Use water to clean up tools and overspray.

### STORAGE AND PACKAGING

VpCI®-373 is available in 5 gallon (19 liter) pails, 55 gallon (208 liter) drums, liquid totes and bulk. Do not let the product freeze.

**FOR INDUSTRIAL USE ONLY**  
**KEEP OUT OF REACH OF CHILDREN**  
**KEEP CONTAINER TIGHTLY CLOSED**  
**NOT FOR INTERNAL CONSUMPTION**  
**CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION**

**LIMITED WARRANTY**

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

**BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.** No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

**THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.**



4119 White Bear Parkway, St. Paul, MN 55110 USA  
 Phone (651) 429-1100, Fax (651) 429-1122  
 Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com  
 Internet <http://www.cortecvci.com>

printed on recycled paper 10% post consumer  
 Revised 4/4/03. Cortec Corporation 1999-2003. All rights reserved. Supersedes: 10/26/00.

Distributed by:



**OTiK Sp. z o.o.**  
 ul. Hutnicza 4  
 81-061 Gdynia  
 tel.: 58 6230498  
 fax: 58 6230496  
[otik@use.pl](mailto:otik@use.pl)  
[www.inhibitory.use.pl](http://www.inhibitory.use.pl)



Certificate No.70781

Certificate No.81867