



## HIGH PERFORMANCE VCI COATINGS

# VCI-819

### PRODUCT DESCRIPTION

VCI-819 Wax/Rinse shines, seals and protects metal surfaces using vapor corrosion inhibitors. VCI-819 is formulated for application in high or low pressure sealer arches in automatic car washes and is safe for all paint finishes. VCI-819 penetrates into finishes, sealing paint and metal surfaces from the damaging effects of corrosion.

VCI-819 provides a lasting shield of protection against sun bleaching, oxidation and corrosive aging of vehicle finishes. VCI-819 also provides corrosion protection for car wash equipment, extending the life of the equipment up to 30%.

### TYPICAL USES

- Available in a ready-to-use version
- Works well on vinyl and plastic parts
- Has excellent sheeting and beading properties on glass
- Contains Vapor Corrosion Inhibitors (VCI)
- Improves gloss on any painted surface after washing with detergent
- Restores color on old painted surfaces
- Provides corrosion/rust protection to car wash equipment
- Is environmentally friendly and nitrite-free
- Protects finishes against UV aging
- Protects painted metal finishes up to 2 months

### APPLICATION

- Cars, motorcycles
- Boats
- House trailers and campers
- Snowmobiles
- Any painted metal surface

### METHOD OF APPLICATION

VCI-819 Wax/Rinse should be applied to painted finishes with high, medium or low pressure spray. No other finishing treatment is necessary before air drying surfaces.

VCI-819 Wax/Rinse can be wiped or buffed off surfaces, creating a deeper shine.

### PHYSICAL PROPERTIES

Appearance	Yellow liquid
Density	7.7-7.9 lb/gal (0.92-0.95 kg/l)
Non-volatile Content	28-35%

### PACKAGING

VCI-819 is available in 5 gallon (19 liter) pails, 55 gallon (208 liter) drums, liquid totes and bulk.

**FOR INDUSTRIAL USE ONLY**  
**KEEP OUT OF REACH OF CHILDREN**  
**KEEP CONTAINER TIGHTLY CLOSED**  
**NOT FOR INTERNAL CONSUMPTION**  
**CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION**

**LIMITED WARRANTY**

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

**BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.** No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

**THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.**



4119 White Bear Parkway, St. Paul, MN 55110 USA  
 Phone (651) 429-1100, Fax (651) 429-1122  
 Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com  
 Internet <http://www.cortecvci.com>

Distributed by:  
**OTiK Sp. z o.o.**  
 ul. Hutnicza 4  
 81-061 Gdynia  
 tel.: 58 6230498  
 fax: 58 6230496



[otik@use.pl](mailto:otik@use.pl)  
[www.inhibitory.use.pl](http://www.inhibitory.use.pl)

